

## Competence CP124S-OCE



### Key features. The optimum for all weighing tasks.

- Verified at the factory for use in legal metrology (EC type-approval certificate). The balance can be used "right out of the box" in legal-for-trade applications after internal calibration | adjustment.
- Innovative all-glass draft shield, with smooth-action doors that open extremely wide; ideally designed for thorough cleaning (removable weighing chamber base plate) and amply sized weighing chamber
- Built-in, motorized calibration weight. For the highest weighing accuracy at the touch of a key.
- Built-in application programs: counting, weighing in %, net-total formulation; animal weighing
- Very easy to operate; all keys feature positive click action; 2 large tare keys; clear and logically arranged keypad
- RS-232 serial interface port
- Excellent, easy-to-read backlit display with especially large digits (16.5 mm)
- Monolithic weigh cell technology – rugged, precise, reliable – year after year
- ISO/GLP-compliant logging of calibration, adjustment and weighing data using an optional data printer or a PC
- Large weighing pan. For more convenience during analytical weighing.
- Four digital filter levels allow the balance to be optimally adapted to the particular ambient conditions at the place of installation


Readability	0.1 mg
Verification scale interval e	0.001 g
Minimum capacity acc. to Directive No. 90/384/EEC	0.01 g
Weighing capacity	120 g
Pan size	Ø 80* mm
Response time (avg.)	2 s
Housing (WxDxH)	213x342x340 mm
Accuracy class	I



Data printer



SartoConnect



\*) Triangular weighing pan shape. Ø = diameter of the inner circle; the shaded area is completely available for use

Key accessories	Order no.
Data printer with date, time and statistics functions	YDP03-OCE
Dust cover for display unit	6960CP04
Data transfer software SartoConnect with RS-232C standard cable (1.5 m);	YSC01L
Anti-static pan	YWP01CP